



SECTION A

SECTION B

SECTION C

SKYLIGHT SPECIFICATION:
 SELF-CURBING, DUAL-GLAZED,
 LOW-PROFILE, FROSTED
 OVER ALUM. SKYLIGHT,
 VARIOUS SIZES.
 LA. R.R. #24822
 L.A. R.R. #24822 A, INC.
 6252 PATTERSON PASS RD., SUITE A
 LIVERMORE, CA 94550
 (800) 88-VELUX

- POOL NOTES:**
- FOR NEW POOL ON SITE, PROVIDE AN ALARM FOR DOORS TO THE DWELLING THAT FORM A PART OF THE POOL ENCLOSURE. THE ALARM SHALL SOUND CONTINUOUSLY FOR A MIN. OF 30 SECONDS WHEN THE DOOR IS OPENED. IT SHALL AUTOMATICALLY RESET AND BE EQUIPPED WITH A MANUAL MEANS TO BE OPERATED FROM THE EXTERIOR OF THE POOL ENCLOSURE. THE DEACTIVATION SWITCH SHALL BE AT LEAST 5'4" ABOVE THE FLOOR.
 - FOR NEW POOL ON SITE, PROVIDE AN ANTHERMAMENT COVER MEETING THE CURRENT CALIFORNIA CODE REQUIREMENTS FOR SWIMMING POOL, TODDLER POOL, AND SPA FOR SINGLE FAMILY DWELLINGS PER THE ASSEMBLY BILL (AB) NO. 2877.
- GARAGE NOTES:**
- DOORS BETWEEN GARAGE AND THE DWELLING UNIT SHALL BE SELF-CLOSING AND SELF-LATCHING, SOLID WOOD OR SOLID OR FIBERGLASS CORE STEEL, NOT LESS THAN 1 1/2" THICK, WITH AN MINIMUM FIRE PROTECTION RATING OF 20 MINUTES. (R302.5.1)
 - THE GARAGE SHALL BE SEPARATED FROM THE DWELLING AND ITS ATTIC AREA IN ACCORDANCE WITH TABLE R302.6 (R302.6)
 - DUCTS PENETRATING THE WALLS OR CEILINGS SEPARATING THE DWELLING FROM THE GARAGE SHALL BE CONSTRUCTED OF A MINIMUM NO. 28 GAGE SHEET STEEL OR OTHER APPROVED MATERIAL AND THERE SHALL BE NO OPENINGS FROM THE DUCTS INTO THE GARAGE.
 - OTHER PENETRATIONS OF GARAGE/DWELLING CEILINGS AND WALLS ARE TO BE PROTECTED AS REQUIRED BY SECTION R302.11, ITEM 4 (R302.5.3)

KLEIN RESIDENCE
SECTIONS

KENNETH DAVID LEE
ARCHITECT A.I.A.
 13844 VENTURA BOULEVARD, SHERMAN OAKS, CA 91423
 (818) 990 - 0391 FAX (818) 990 - 3749

REVISIONS:	BY
08.01.12 JG	JG
08.02.12 JG	JG
08.09.12 JG	JG

DATE: 04.23.12
 SCALE: 1/4" = 1'-0"
 DRAWN:
 JOB:
 SHEET:
A-6
 SHEETS